

GLOBEPHAROS



GP15-18

Diesel Forklift

CE
CE CERTIFICATE

MAIN SPECIFICATIONS

General	1	Model		GP15-JBN	GP18-JBN	
	2	Power Type		Diesel		
	3	Rated Load Capacity	Q(kg)	1500	1800	
	4	Load Centre	C(mm)	500		
Characteristic & Dimension	5	Rated Lift Height	H3(mm)	3000		
	6	Free Lift Height	H2(mm)	100		
	7	Fork Size (L×W×T)	mm	920×120×35	1070×120×40	
	8	Mast Tilt Angle (F/R, α°/β°)	deg	6°/12°		
	9	Fork Overhang (Wheel Center to Fork Face)	X1(mm)	409		
	10	Rear Overhang	X2(mm)	470		
	11	Ground Clearance (Bottom of Mast)	H7(mm)	110		
	12	Length to Face of Fork (Without Fork)	L1(mm)	2285		
	13	Overall Width	B1(mm)	1082		
	14	Mast Lowered Height	H1(mm)	2025		
	15	Mast Extended Height (With Backrest)	H4(mm)	4055		
	16	Overhead Guard Height	H5(mm)	2160		
	17	Turning Radius (Outside)	Wa(mm)	2100		
	18	Min.Aisle width for pallets	mm	3700		
Performance	19	Travel Speed (No Load)	km/h	14.5		
	20	Lifting Speed (Full Load)	mm/sec	560		
	21	Max.Gradeability (Full Load)	%	20		
	22	Wheelbase	Y(mm)	1410		
	23	Tyre (Front x 2)	mm	6.50-10-10PR		
24	Tyre (Rear x 2)	mm	5.00-8-10PR			
Weight	25	Total Weight	kg	2860	2990	
	26	Front Axle Weight Distribution (Full Load/No Load)	kg	3815/1200	4120/1170	
	27	Rear Axle Weight Distribution (Full Load/No Load)	kg	545/1660	720/1820	
Power & Transmission	28	Battery	V/Ah	12/90		
	29	Engine Model		C240NKFC-01		
	30	Engine Manufacturer		ISUZU		
	31	Rated Output / r.p.m.	kw	34.5/2500		
	32	Transmission Type		Powershift (Manual)		
	33	Transmission Stage (FWD/RVS)		1/1(2/2)		
	34	Operating Pressure (For Attachments)	Mpa	14.5		

